


Broadband Horn Antenna – HAX-18, 800 MHz – 18 GHz

for immunity tests and emission measurements



Description

The horn antennas HAX offer a very low SWR in their nominal frequency range and a very broad bandwidth. The gain increases with frequency up to approx. 16 dBi. The increasing gain with frequency helps to compensate cable losses.

The HAX series is suitable for both, transmission and receiving applications. The maximum allowed input power is only limited by the female N-connector. The detailed manual of the calibrated test antennas includes gain, antenna factor, SWR and directional patterns. The antenna is mounted with the 22 mm tube, equipped with a index ring for quick changes of polarization without using tools.

Technical specifications

Type:	HAX-18
Frequency range:	800 MHz to 18 GHz
Max. input power	limited only by N-connector
Connection:	N-female
Isotropic gain:	6 ... 16 dBi
Antenna factor:	24 ... 50 dB/m
Nominal impedance:	50 Ohm
SWR typical:	≈ 1.5
Front to back ratio:	> 25 dB ($f > 1.3$ GHz)
Cross polarization rejection:	> 25 dB (1 GHz ... 18 GHz)
3dB Beamwidth typ. (E-plane):	90° - 10°
3dB Beamwidth typ. (H-plane):	60° - 10°
Dimensions (L x W x H) in mm:	408 x 245 x 142
Weight:	1.3 kg
Fixation:	∅ 22 mm tube
Use:	Radiated immunity tests Emission measurements

Measurements

