

Broadband Horn Antenna – HAX-6, 500 MHz – 6 GHz

for immunity tests and emission measurements



Description

The horn antennas HAX offer a very low SWR in their nominal frequency range and a very broad bandwidth. The gain increases with frequency up to approx. 18 dBi. The increasing gain with frequency helps to compensate cable losses.

The HAX series is suitable for both, transmission and receiving applications. The maximum allowed input power is only limited by the female N-connector. The detailed manual of the calibrated test antennas includes gain, antenna factor, SWR and directional patterns. The antenna is mounted with the 22 mm tube, equipped with a index ring for quick changes of polarization without using tools.

Technical specifications

| | |
|-------------------------------|--|
| Type: | HAX-6 |
| Frequency range: | 500 MHz to 6 GHz |
| Max. input power: | limited only by N-connector |
| Connector: | N-female |
| Gain: | 6 ... 18 dBi |
| Antenna factor: | 19 ... 29 dB/m |
| Standing wave ratio SWR typ.: | < 2 |
| Dimensions (L x W x H) in mm: | 820 x 424 x 314 |
| Weight: | 4.1 kg |
| Fixation: | ∅ 22 mm tube |
| Material: | aluminium |
| Use: | Radiated immunity tests Emission measurements |

Measurements

