


Technical Specification




Frequency Range(GHz)	2.0 - 4.0		
Gain(dB)	15 Typ.		
Polarization	Linear		
VSWR	2.0 max		
Waveguide	WR320		
Connector	N-F		
Size(mm)	264 x 204 x 377		
Net Weight(Kg)	1.6 Around		

Outline Drawing (Size: mm)






Flange Drawing (Size: mm)






Test Results

1. Gain and Antenna Factor









Frequency	Gain	Antenna Factor	Frequency	Gain	Antenna Factor
(GHz)	(dB)	(dB/m)	(GHz)	(dB)	(dB/m)
2.0	13.57	22.66	3.1	16.54	23.50
2.1	13.85	22.80	3.2	16.71	23.60
2.2	14.06	23.00	3.3	17.08	23.50
2.3	14.33	23.11	3.4	17.09	23.75
2.4	14.89	22.92	3.5	17.1	23.99
2.5	14.91	23.26	3.6	17.16	24.18
2.6	15.39	23.12	3.7	17.26	24.31
2.7	15.53	23.31	3.8	17.33	24.48
2.8	15.42	23.73	3.9	17.62	24.41
2.9	15.83	23.63	4.0	16.76	25.49
3.0	16.18	23.57	-	-	- 10

2. VSWR





3. Cross Polarization Isolation



4. Pattern

