



# PSSA-0.8G4.2G-250

## 250W CW SS Amplifier

### Solid State Power RF Amplifier

The PSSA-0.8G4.2G-250 is a Solid State 250W (CW) RF Amplifier which covers frequency range from 0.8GHz to 4.2GHz. This amplifier can achieve high efficiency operation with proven reliability as is designed with the robust engineering and employment of the most advanced devices and components. The amplifier comes with 1 year warranty.

Parameter	Specification
<b>Electrical</b>	
Frequency Range	0.8-4.2GHz
Output Power	300W CW SAT min., 250W @ P1dB
Internal Protection	Up to 0dBm with no damage
Gain @ rated power	55dB min.
Gain Adjustment	0 to 20dB
Input /Output Impedance	50 ohms(VSWR 2.0:1)
RF Input / Output Connectors	Type N Female Input Type 7/16 Female Output
Modulation	AM / FM / Pulse
Spurious	-50dBc
Harmonics	-20dBc @ P1dB
Prime Power	115Vac / 220Vac +/-10%, 50/60 Hz, Three Phase, 5 wires
Power Consumption	6.5KVA
<b>Mechanical</b>	
Configuration	Rack 22"W x 36.13"D x 20U panel space
Cooling System	Air cooled ,self contained
Shock	MIL-STD-810C, method 516.2
Vibration	MIL-STD-810C, method 514.2
Temperature	0° to 45°C
Non-operating temp	0° to 60°C
Humidity	95% without condensation
Altitude	10, 000 feet

THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



## Features [Build-in]

- VSWR Protection with Power Fold back when VSWR is greater than 3:1.
- RS 232 & Ethernet Remote Control.
- Gain Control.
- Leveling Control [ALC].
- Internal Pre-Amp.
- RF Input / Output Connectors on the Front Panel.
- Standby/RF\_ON, Elapsed Time Metering in hours.
- Color TFT Touch screen Display with Front Panel Controls and Indicators.

## OPTIONS

- 001 VSWR Protection against any output mismatch greater than 6:1; will operate without damage or oscillation against any magnitude and phase of source and load impedance.
- 002 Alternate Prime Power (specify at time of order).
- 003 Pin-Diode Pulse Modulation.
- 004 Forward RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel.
- 005 Reflected RF Sample Port Type N Female -50dBc nominal on the Front or Rear Panel.
- 006 RF Input / Output Connectors on the Front /Rear Panel (Specify front or rear at time of order).
- 007 Gain Equalizer.
- 008 Input Power Limiter.
- 009 RF Safety Interlock, type BNC Connector.
- 010 Slides for Rack mount.

Distributed by

### **Reliant EMC LLC**

3311 Lewis Ave  
Signal Hill, CA 90755  
Tel.:(408)9165750

**E-Mail: [contact@reliantemc.com](mailto:contact@reliantemc.com)**

**Web:[www.reliantemc.com](http://www.reliantemc.com)**

*THESE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.*